orivue

TURRET · DUAL LIGHT

OV-NG6TS1-DA28

6MP Dual-Light Compact Turret

- 6MP (3072 × 2048) real-time video at 30 fps, H.265 / H.264
- Dual-light night vision: infrared or warm white light, auto / manual / off
- True WDR for scenes with strong backlight
- Built-in microphone and speaker for two-way audio
- Smart analytics: intrusion, line crossing, loitering, personnel absence, illegal parking
- ONVIF Profile S / T / G for third-party NVRs; built-in PoE



6MP

Dual Light · True WDR · Two-Way Audio · PoE · MicroSD · Smart Analytics · ONVIF

RESOLUTION	SENSOR	NIGHT VISION	LENS
6MP	1/2.7"	Dual light	2.8 mm

Pair with the OV-JB120 junction box for a clean installation: connectors and cable slack stay inside the box, and the side conduit entry keeps surface-run cable tidy.



RECOMMENDED ACCESSORY

OV-JB120 Junction Box

Ø4.75 × 1.91 in (Ø120.6 × 48.4 mm) · conceals connectors and cable slack · side conduit entry

OV-NG6TS1-DA28

6MP Dual-Light Compact Turret · Technical Specifications

orivue


CAMERA	
Image sensor	1/2.7" progressive scan CMOS
Minimum illumination	0.01 lux
Lens	Fixed 2.8 mm, F1.6, M12 mount
Field of view	H 108.3° / V 59.9° / D 126.8°
Day / night	ICR; auto / color / B&W / external trigger / scheduled
Supplement light	IR + warm white dual light; auto / manual / off; brightness 0–100
Supplement light distance	IR 131 ft (40 m) / warm light 98 ft (30 m)
Shutter	Auto electronic shutter

VIDEO	
Compression	H.265 / H.264, dual stream
Main stream	3072 × 2048 / 2880 × 1620 / 2560 × 1440 / 2304 × 1296 / 1920 × 1080 @ 30 fps
Sub stream	D1 / VGA / 864 × 480 / 640 × 360 @ 30 fps
Bitrate control	CBR / VBR
OSD	Time, title, multi-line text


IMAGE	
WDR	True WDR; digital WDR
Exposure	BLC / HLC; shutter priority / gain priority
3D DNR	Off / Low / Medium / Higher / High
Defog	Supported
Image adjustment	Brightness, contrast, sharpness, saturation, hue
Mirror	Off / horizontal / vertical / 180° rotation
Privacy mask	4 areas

SMART	
AI events	Region intrusion, line crossing, loitering, personnel absence, illegal parking (person / vehicle)
Smart light control	No dimming / dim on person / dim on license plate
Motion detection	Full screen or region, multi-level sensitivity
Tamper alarm	1 area
Exception alarm	Network disconnected, IP conflict, illegal access
Event linkage	Email, light alarm, sound alarm

DIMENSIONS (DRAWING IN MM)



Front · Ø4.41 in (112 mm)



Side · 3.62 in (92 mm)

AUDIO	
Audio	Built-in microphone and speaker, two-way audio
Audio compression	G.711u / G.711A

NETWORK	
Interoperability	ONVIF Profile S / T / G, RTSP
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, RTMP, DDNS, UPnP, FTP
Security	User authentication, HTTPS, AES connection encryption, RTSP authentication
Live view	Up to 4 simultaneous streams
Remote access	Web browser, mobile app, PC client

INTERFACE	
Network	RJ45, 10/100M auto-negotiation
Power	DC 12 V / PoE
Storage	MicroSD card slot
Reset	Supported

GENERAL	
Housing	Compact Turret, Aluminum alloy, powder coated, white
Dimensions	Ø4.41 × 3.62 in (Ø112 × 92 mm)
Ingress protection	IP67
Weight	0.88 lb (400 g)
Operating temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Operating humidity	0–90% RH
Compliance	NDAA Section 889

ORDERING INFORMATION

OV-NG6TS1-DA28	6MP Dual-Light Compact Turret, 2.8 mm
OV-JB120	Junction Box (optional)